



 greenpaper®

Ecowhite®

White Top Liner

Discover Ecowhite®, the perfect solution for your printing needs. This innovative multi-ply linerboard combines a white printing surface with a kraft back, making it ideal for direct printing applications.

Manufactured in ISO-certified mills, it guarantees premium quality and high-end appearance.



PRODUCT OVERVIEW

White top liner with brown back.


KEY FEATURES

- Moderate resistance to water absorption.
- Resistant to bursting or compression under a given applied force.
- Made from 100% recycled fibrous material.

RECOMMENDED APPLICATIONS

- Inner or outer layer of a corrugated box structure.
- **Applications:** Agricultural, industrial, and packaging.
- Suitable only for flexographic or rotogravure printing.

LAYER STRUCTURE



1. Face (white fiber)
2. Back (brown fiber)



		LCB 150	LCB 160	LCB 180	LCB 205	Tolerance	TAPPI Method
Basis Weight	g/m²	150	160	180	205	+/-5%	T-410
Basis Weight	lb/1000 ft²	30.72	32.77	36.87	41.99	+/-5%	T-410
Ring Crush CM	lbf/6in	40	42	50	60	Minimum	T-822
Moisture	%	6	6	6	6	+/-1	T-412
Brightness	GE	78	78	78	78	Minimum	T-452
Cobb Test	g/m²	60	60	60	60	+/-10	T-441
Ply-Bond	lbs/in²	90	90	90	90	Minimum	T-541

OBSERVATIONS

All physical properties are measured under controller conditions (23°C and 50% relative humid) values provided are for quality control purposes, based on factory reel samples.

FINISHING SPECIFICATIONS

- Reel & pallet tolerance: +/-1 mm.
- Reel diameter tolerance: +/- 2in.
- Joints: Max. 2 per reel, no joints within 20 cm of final winding.
- Winding uniformity: Max 1 cm uneven winding.
- Core protrusion: Not exceeding 1 cm on either side.
- Edge cut quality: Clean cut, free of residue.